

Senior Checker Last Name

Child Passenger Safety Checklist

Use blue, black, or #2 pencil, and for mistakes, use white-out correction tape.

Fill in boxes from left to right, one letter/number per box: 1 2 3 A B C

Fill in circles like this: Caregiver Last Name Street Address City Phone Email Address Vehicle Year Vehicle Make/Mfg. (e.g. Vehicle Model (e.g. Malibu, Enclave) Today's Date **STOP HERE** · CHILD NUMBER ONE · O Days Weight (lbs) Height Child Present O Unborn O Yes O No Child's Age O Month(s) Seat Checked Before? O Yes O No O Year(s) Child First Name Child's DOB 22. CSS Manufacturer **FINDINGS** ON ARRIVAL Yes No N/A OSame as 4, 5, 6 (Mark - Go to #25) 1. Child/CSS Location in Vehicle 0 7. CSS History Known 0 OBritax DOO Front Row Other Seating Location OBaby Trend 8. CSS Involved in a Crash **O**Combi 0 0 **O**Chicco OOO Back **O**Evenflo **O**Graco 9. CSS Labels Missing 0 0 OHarmony ${\color{red}\mathsf{OMagna/Clek}}$ **000** 3rd Row 10. CSS Expired 0 0 2. CSS Installed Using (select all that apply) OOrbit. OPeg Perego 11. CSS Recalled 0 0 ORecaro OSunshine Kids/Diono ONo CSS (Mark - Go to #18) OIntegrated Seat 12. CSS Correct Direction 0 OLearning Curve - 1st Years **O**Uninstalled 0 ODorel (Cosco, Edie Bauer, Safety 1st, Maxi Cosi) **O**Seatbelt 13. CSS Harness Correct 0 0 0 OOther | **O**Tether 14. Recline Angle Correct 0 0 0 **O**Lower Anchors 23. Model Number 15. Lower Anchors Correct 0 0 0 3. Restraint Type ORF Only w/o Base ORF Only w/ Base 16. Tether Correct 0 0 0 24. Manufacture Date (MM/DD/YY) OBase Only **O**RF Convertible 17. Seatbelt Correct 0 0 **O**BP Booster OFF w/ Harness OLap Only ON DEPARTURE OLap/Shoulder 25. ALL CORRECTIONS MADE? O Yes O No 18. Child/CSS Location in Vehicle 26. CSS/Vehicle Compatible? O Yes O No OCar Bed **O** Vest D O O Front Row O Other Seating Location 27. Educational Materials Given? O Yes O No 4. CSS Manufacturer OOO Back TECHNICIAN DISCUSSED OBaby Trend **O**Britax **O**Chicco **O**Combi **000** 3rd Row **O**Airbags **O**Evenflo OGraco. **O**Unused Seatbelt 19. CSS Installed Using (select all that apply) **O**Harmony OMagna/Clek **O**Projectiles $ON_0 CSS$ OIntegrated Seat **O**Orbit OPeg Perego OUnattended Children in/around Cars **O**Uninstalled ORecaro OSunshine Kids/Diono **O**Next Steps **O**Seatbelt OLearning Curve - 1st Years Caregiver Sign-Off: No N/A O Tether ODorel (Cosco, Edie Bauer, Safety 1st, Maxi Cosi) I harnessed Child in CSS **O**Lower Anchors I participated/installed CSS today O OOther | 20. OPRC Provided a New CSS? O Yes O No 21. Restraint Type Caregiver Initials Donation \$ 5. Model Number ORF Only w/ Base ORF Only w/o Base Comments **O**RF Convertible OBase Only 6. Manufacture Date (MM/DD/YY) OFF w/ Harness **O**BP Booster OLap/Shoulder OLap Only OCar Bed **O** Vest Tech Last Name Tech Number O No Misuse



Senior Checker Number

O New Install

__ Paid for Seat

CHILD NUMBER TWO			
Child Present O Ur Seat Checked Before Child First Name	nborn O Yes O No ? O Yes O No	Child's Age O Days O Month(s) O Year(s)	Height Weight (lbs.)
ON ARRIVAL		FINDINGS Yes No N/A	22. CSS Manufacturer OSame as 4, 5, 6 (Mark - Go to *25)
1. Child/CSS Location in Vehicle		7. CSS History Known	OBaby Trend OBritax
	Other Seating Location Explain:	8. CSS Involved in a Crash O	OChicco OCombi
OOO Back		9. CSS Labels Missing O O	O Evenflo O Graco
0 0 0 3rd Row		10. CSS Expired O O	OHarmony OMagna/Clek
	g (select all that apply)		OOrbit OPeg Perego
ONo CSS (Mark - Go to #18) OIntegrated Seat		11. CSS Recalled	ORecaro OSunshine Kids/Diono
OUninstalled	(I-lark - Go to - /)	12. CSS Correct Direction O O	OLearning Curve - 1st Years ODorel (Cosco, Edie Bauer, Safety 1st, Maxi Cosi)
OSeatbelt OTether		13. CSS Harness Correct O O O	OOther Cosco, Edie Dauer, Safety Ist, Maxi Cosi)
OLower Anchors		14. Recline Angle Correct O O	23. Model Number
3. Restraint Type		15. Lower Anchors Correct O O O	23. Floder Rumber
ORF Only w/o Base	ORF Only w/ Base	16. Tether Correct O O	24. Manufacture Date (MM/DD/YY)
OBase Only	ORF Convertible	17. Seatbelt Correct O O O	24. Manufacture Date (MM/DD/11)
OFF w/ Harness	OBP Booster		
OLap/Shoulder (Mark - Go to #17)	OLap Only (Mark - Go to # 17)	ON DEPARTURE	25. ALL CORRECTIONS MADE? O Yes O No
OCar Bed OVest		18. Child/CSS Location in Vehicle	26. CSS/Vehicle Compatible? O Yes O No
4. CSS Manufacturer		DOO Front Row Other Seating Location	27. Educational Materials Given? O Yes O No
OBaby Trend	OBritax	OOO Back	TECHNICIAN DISCUSSED
O Chicco	O Combi	0 0 0 3rd Row	O Airbags
O Evenflo	OGraco	19. CSS Installed Using (select all that apply)	OUnused Seatbelt
OHarmony	OMagna/Clek	ONo CSS OIntegrated Seat	O Projectiles
OOrbit	O Peg Perego	Ouninstalled	OUnattended Children in/around Cars
ORecaro	OSunshine Kids/Diono	OSeatbelt	ONext Steps
OLearning Curve - 1st Years ODorel (Cosco, Edie Bauer, Safety 1st, Maxi Cosi)		OTether	Caregiver Sign-Off: Yes No N/A
Oother		OLower Anchors	I harnessed Child in CSS OOO OI participated/installed CSS today OOO
5. Model Number		20. OPRC Provided a New CSS? O Yes O No 21. Restraint Type	Caregiver Initials Donation \$
5. Model Number		ORF Only w/o Base ORF Only w/ Base	Caregiver initials Donation \$
		OBase Only ORF Convertible	Comments
6. Manufacture Date (MM/DD/YY)		OFF w/ Harness OBP Booster	
		OLap/Shoulder OLap Only	
		OCar Bed OVest	
Task Name			
Tech Last Name	, , , , , , , , , , , , , , , , , , , 	Tech Number	O No Misuse
			2
Senior Checker Last Name Senior Checker Number O New Install			
			5.46.0
			\$ Paid for Seat
OUICK DEEEDENIGE			

Direction

Babies less than 2 should ride in a rear-facing position to protect the spine and neck. Babies who have outgrown the infant only child restraint (CR) should switch to a convertible CR and use it rear-facing up to highest height or weight (usually 30 - 45 lbs) permitted by the manufacturer. At a minimum, children MUST be age 1 and 20 lbs before facing forward. CR selection may be limited by what fits in the vehicle.

Location

Harness

All Children under age 13 should ride in a back seat. If a child must ride in the front seat, then the child with a full harness CR or properly adjusted shoulder belt, seated in the correct forward facing and upright position, should sit there. Move the vehicle seat back as far away from the airbag as possible. For older children sitting in safety belts next to side airbags, remind them to sit straight up and avoid resting their heads on a window or structural pillar of the vehicle.

Rear-facing CR harness straps should pass through the slots at or below the child's shoulders. The forward facing CR harness straps should pass through the slots at or above the child's shoulders. Red CR instructions. Use all CRs until the upper height or weight limits are met. A child is too large for the CR when the shoulders are above the top FF harness slots, the child's head is within 1 inch of the top of the rear facing CR or he exceeds the CR weight or height limits. Harness straps must lay flat on the chest and over the hips. Harness straps must pass the "pinch" test: when the buckled straps are pinched at the shoulder, there should be no slack or extra webbing. The harness retainer clip must sit at the child's armpit level, and the straps must be threaded properly through the clip.

Belt-Positioning Booster (BPB) Seats

Use all BPBs with vehicle lap/shoulder safety belts. Check BPB instructions for use with switchable should belts. Special products such as vests and Y-harnesses used with a booster base, must be used according to the manufacturer's instructions and the vehicle owner's manual. Many children will be between 8 - 12 years before the safety belt alone fits properly. Use a BPB until that time.

Fully read the vehicle and CR manufacturer's instructions. In most cases use either LATCH or safety belts, not both together. There are a few BPB that use both lower anchors for the BPB and a seat belt for the child. Never install a rear-facing CR in front of an airbag. Even if the passenger sensing system or airbag switch has been turned off for the right front passenger frontal airbag, no system is fail-safe. Secure rear-facing CRs in a back seat. Follow manufacturers instructions. Safety belts must pass through the CR exactly where and how the manufacturer directs. CRs must not move more than 1 inch side to side or front to back when grasped at the belt path. LATCH anchors are used only if both the vehicle and CR are equipped. Check vehicle manual to identify designated LATCH and tether locations. Always use the top tether as directed by the manufacturer and the vehicle owner's manual. Tethers are never attached to the lower anchor bars. Use tethers on a rear-facing CR only if the manufacturer so directs. Vehicles made after 1996 meet federal safety belt lockability requirements; no locking clip should be needed. Test vehicle safety belts to be sure they are locked at either the retractor or latchplate. Tethers may be used in some vehicles to 40 or 48 lbs (weight of child) and in others to 60 lbs (weight of child plus CR). Heavier children who ride in a harnessed CR require special arrangements. Check with the vehicle manufacturer. Treat unused safety belts as you would any other cords. They are not toys and can be hazardous if used for any purpose other than restraint.

Child Ready for Safety Belt

With the child's back and bottom against the vehicle seat back, the knees should bend naturally at vehicle seat edge. When the safety belt is buckled, the lap belt fits low on the hips, touching the thighs, and the should belt rests between the neck and shoulder on the collarbone. Never place the shoulder belt under arms or behind backs. Optimally, the child's feet should touch the floor.

Remind Caregivers to NEVER LEAVE A CHILD ALONE IN A CAR. The CR is not a babysitter. Children should not spend excessive amounts of time in a CR when outside of a vehicle.