



**Titan SureRide 65™ Convertible Car Seat – factory select**  
 Rear Facing 5-40 lbs. (2,3-18 kg) Ht 19”-40” (48-94 cm)  
 Forward Facing 22-65 lbs. (10-29,4 kg) Ht 28”-54” (71-137 cm)  
 Factory Select - # 3712198 two pack

**Rear-facing for infants, and when ready, converts to forward-facing.**

Keep your growing child safe and comfortable in Evenflo’s Titan SureRide 65 convertible car seat. With a rear-facing weight rating up to 40 lbs. and a forward-facing weight rating up to 65lbs. your child can remain harnessed longer!

**Protecting children is our core mission at Evenflo.**

For almost a century we have been a leader in safety, innovation and education. Knowing that one in four automobile accidents are side impact collisions, we go beyond the current government standards when designing the next generation of Evenflo car seats.

The top of the child's head must be at least 1 inch below the top of the child restraint seat back

## Fashion will Vary

## Product Features

**65 lbs.. Internal Harness** extends product life for the child

**Up-Front Adjust** – Easy Access Harness tension system

**5-point harness** provides proper fit

**Pad removes easily** for machine-washing

**6 shoulder harness positions** and **2 crotch buckle positions** for better fit and longer use

Seat to top harness slot: 19 ¼”

Seat to bottom harness slot: 6 ½”

**Infant Insert Included**

**Side Impact Tested!** Meets or exceeds all applicable Federal Safety Standards AND Evenflo’s Side Impact Test Standard

**Designed and tested** for structural integrity at energy levels approximately 2X the federal crash test standard

**Energy absorbing foam liner** provides added safety & comfort

**FMVSS 213:** Federal Motor Vehicle Safety Standards for Child Restraint Systems

**FMVSS 302:** Federal Motor Vehicle Safety Standards for Flammability of Interior Materials

**Certified For Use In Aircraft:** This restraint meets FAA Inversion requirements for airplane use

## Safety Testing

**Side Impact Tested!** Meets or exceeds all applicable Federal Safety Standards and Evenflo’s side impact standards. Designed and tested for structural integrity at energy levels approximately 2x the federal crash test standard.

FMVSS 213: Federal Motor Vehicle Safety Standards for Child Restraint Systems

FMVSS 302: Federal Motor Vehicle Safety Standards for Flammability of Interior Materials

Certified for Use in Aircraft: This restraint meets FAA Inversion requirements for airplane use.

## Child Specifications

**Rear Facing**

**Weight:** 5 – 40 lbs. (2,3 – 18,0 kg)

**Height:** 19 – 40 in. (48 – 94 cm)

The top of the child’s head must be at least 1 inch below the top of the child restraint seat back

**Forward Facing**

**Weight:** 22 – 65 lbs. (10 – 29,4 kg)

**Height:** 28 – 54 in. (71 – 137 cm)

**Age:** minimum of two years of age

## Use & Care

Carefully read all instructions and warnings on the product, product labels, and instruction manuals before use. Consult your vehicle owner’s manual to determine proper placement of child restraint in your vehicle and familiarize yourself with your vehicle’s components.

### Cleaning Instructions

- To clean pads slide the plastic clips on the seat pad off of the seat shell.
- Cloth pads and canopies may be machine washed separately – cold water, delicate cycle, tumble dry 10 – 15 minutes, low heat.
- Wipe straps, buckles and harness adjuster with warm damp cloth and mild soap. Air dry.
- To help protect the vehicle upholstery, place a towel beneath and behind the child restraint.

## Product Specifications

Carton Dimensions (inches): 32.75” H x 21” W x 18.25” D In.

Carton Dimensions (cm): 83.19 H x 53.34 W x 46.36 D cm

Assembled Product Dimensions (inches): 28” H x 20” W x 19.25” D cm

Assembled Product Dimensions (cm): 71.12 H x 50.8 W x 48.89 D cm

Product Weight: 14 lbs.. ( 6.35 kg)

Shipping Weight: 31 lbs.. ( 14.06 kg)

Model Number: 3712198

Packaging: 2 pack Carton

UPC Number: TBD

FOB Number: Piqua

Pattern: Factory Select

(gender neutral)

**All Evenflo products have transitioned to a 2-year age minimum for forward-facing use.**

