

CHILD RESTRAINTS REQUIRED FOR CHILDREN THROUGH AGE 5 in Motor Vehicles Effective January 1, 2015

Florida Statute 316.613 states every driver of a motor vehicle must:

- protect children through age 5 (formerly age 3) by properly using a child restraint device
- comply or receive a moving violation, 3 points on driver's license, and a minimum \$60 fine plus court costs and fees

Proper Installation Recommendations

Choose a Car Seat to Fit the Child and Vehicle

Make sure the car seat is designed to fit your child's current height and weight, and will suffice as your child grows. Test the car seat you plan to buy to make sure it fits well in your vehicle. Not all car seats fit in all vehicles.

Read the Car Seat and Vehicle Manuals

Every car seat is different. Every vehicle is different. Read the car seat manual for either LATCH or seat belt installation, as well as the vehicle manual's section on installing car seats in that particular position in the vehicle.

Secure the Car Seat to the Vehicle

Car seat should not move more than 1 inch when pulled at the belt path. Check for a correct recline angle if rear facing; if forward facing, connect the top tether strap. The back seat is the safest position, away from direct crash impacts and air bags.

Secure the Child in the Car Seat

Harness straps lie flat, not twisted, and snug enough so that extra material cannot be pinched at the shoulder. Rear facing straps should be at or below your child's shoulders; forward facing should be at or above. The chest clip should be at armpit level.

NEED ASSISTANCE?

Contact the Florida Occupant Protection Resource Center to find a fitting station near you with certified CPS Technicians to ensure correct car seat installation.

352-273-1671 * floridaoprc.ce.ufl.edu

Funded by Florida Department of Transportation

CHILD RESTRAINTS REQUIRED FOR CHILDREN THROUGH AGE 5 in Motor Vehicles Effective January 1, 2015

Florida Statute 316.613 states every driver of a motor vehicle must:

- protect children through age 5 (formerly age 3) by properly using a child restraint device
- comply or receive a moving violation, 3 points on driver's license, and a minimum \$60 fine plus court costs and fees

Proper Installation Recommendations

Choose a Car Seat to Fit the Child and Vehicle

Make sure the car seat is designed to fit your child's current height and weight, and will suffice as your child grows. Test the car seat you plan to buy to make sure it fits well in your vehicle. Not all car seats fit in all vehicles.

Read the Car Seat and Vehicle Manuals

Every car seat is different. Every vehicle is different. Read the car seat manual for either LATCH or seat belt installation, as well as the vehicle manual's section on installing car seats in that particular position in the vehicle.

Secure the Car Seat to the Vehicle

Car seat should not move more than 1 inch when pulled at the belt path. Check for a correct recline angle if rear facing; if forward facing, connect the top tether strap. The back seat is the safest position, away from direct crash impacts and air bags.

Secure the Child in the Car Seat

Harness straps lie flat, not twisted, and snug enough so that extra material cannot be pinched at the shoulder. Rear facing straps should be at or below your child's shoulders; forward facing should be at or above. The chest clip should be at armpit level.

NEED ASSISTANCE?

Contact the Florida Occupant Protection Resource Center to find a fitting station near you with certified CPS Technicians to ensure correct car seat installation.

352-273-1671 * floridaoprc.ce.ufl.edu

Funded by Florida Department of Transportation

CHILD RESTRAINTS REQUIRED FOR CHILDREN THROUGH AGE 5 in Motor Vehicles Effective January 1, 2015

Florida Statute 316.613 states every driver of a motor vehicle must:

- protect children through age 5 (formerly age 3) by properly using a child restraint device
- comply or receive a moving violation, 3 points on driver's license, and a minimum \$60 fine plus court costs and fees

Proper Installation Recommendations

Choose a Car Seat to Fit the Child and Vehicle

Make sure the car seat is designed to fit your child's current height and weight, and will suffice as your child grows. Test the car seat you plan to buy to make sure it fits well in your vehicle. Not all car seats fit in all vehicles.

Read the Car Seat and Vehicle Manuals

Every car seat is different. Every vehicle is different. Read the car seat manual for either LATCH or seat belt installation, as well as the vehicle manual's section on installing car seats in that particular position in the vehicle.

Secure the Car Seat to the Vehicle

Car seat should not move more than 1 inch when pulled at the belt path. Check for a correct recline angle if rear facing; if forward facing, connect the top tether strap. The back seat is the safest position, away from direct crash impacts and air bags.

Secure the Child in the Car Seat

Harness straps lie flat, not twisted, and snug enough so that extra material cannot be pinched at the shoulder. Rear facing straps should be at or below your child's shoulders; forward facing should be at or above. The chest clip should be at armpit level.

NEED ASSISTANCE?

Contact the Florida Occupant Protection Resource Center to find a fitting station near you with certified CPS Technicians to ensure correct car seat installation.

352-273-1671 * floridaoprc.ce.ufl.edu

Funded by Florida Department of Transportation

CHILD RESTRAINTS REQUIRED FOR CHILDREN THROUGH AGE 5 in Motor Vehicles Effective January 1, 2015

Florida Statute 316.613 states every driver of a motor vehicle must:

- protect children through age 5 (formerly age 3) by properly using a child restraint device
- comply or receive a moving violation, 3 points on driver's license, and a minimum \$60 fine plus court costs and fees

Proper Installation Recommendations

Choose a Car Seat to Fit the Child and Vehicle

Make sure the car seat is designed to fit your child's current height and weight, and will suffice as your child grows. Test the car seat you plan to buy to make sure it fits well in your vehicle. Not all car seats fit in all vehicles.

Read the Car Seat and Vehicle Manuals

Every car seat is different. Every vehicle is different. Read the car seat manual for either LATCH or seat belt installation, as well as the vehicle manual's section on installing car seats in that particular position in the vehicle.

Secure the Car Seat to the Vehicle

Car seat should not move more than 1 inch when pulled at the belt path. Check for a correct recline angle if rear facing; if forward facing, connect the top tether strap. The back seat is the safest position, away from direct crash impacts and air bags.

Secure the Child in the Car Seat

Harness straps lie flat, not twisted, and snug enough so that extra material cannot be pinched at the shoulder. Rear facing straps should be at or below your child's shoulders; forward facing should be at or above. The chest clip should be at armpit level.

NEED ASSISTANCE?

Contact the Florida Occupant Protection Resource Center to find a fitting station near you with certified CPS Technicians to ensure correct car seat installation.

352-273-1671 * floridaoprc.ce.ufl.edu

Funded by Florida Department of Transportation